



ONE™ GUIDE SPECIFICATION

INTRODUCTION

Comac Corporation, Inc. manufactures and distributes warm air hand dryers for public and commercial washrooms. The Company recognized the need for a hand dryer that would embody the best attributes of all models currently on the market but would also include next-generation features to achieve unprecedented performance, durability, attractiveness and value. The result of Comac Corporation's design and development is the **ONE™** Hand Dryer.

The **ONE™** meets or exceeds all industry standards for high-quality hand dryers. It generates over 150 CFM of air at [136 degrees F] [58 degrees C] to fully dry the hands in approximately 30 seconds. The airflow is emitted by a low-RPM large-diameter fan producing less than 70 dB and with an expected average lifespan of more than 20 years. The **ONE™** sets the standard for low noise and high performance.

Despite its power, the **ONE™** Hand Dryer consumes only 1450 watts. In addition to the energy savings versus 2000-watt models, the 12.6 amp at 115 VAC rating allows the **ONE™** to be installed on a standard 15-amp branch circuit. The **ONE™** also incorporates Comac's exclusive universal-voltage technology, instantly and automatically adjusting to 115, 208 or 230 VAC, 50/60 Hz input power sources.

The **ONE™** is a surface-mounted hand dryer that protrudes only [4 inches] [100 mm] from the wall for a sleek and attractive appearance that conforms to ADA requirements. The cover of the **ONE™** is constructed of die-cast zinc and heavy-gauge stamped steel, allowing for a variety of available surface finishes including chrome, scratch-resistant porcelain enamel, and brushed stainless steel.

The **ONE™** is the world's first modular dryer. The entire mechanism is contained in a plug-in "power pack" that can be replaced in minutes without special tools or electrician's fees. The durable **ONE™** also carries an industry-leading 10+2 year warranty.

This guide specification, SECTION 10811 - RAPID DRYING ELECTRIC HAND DRYER, has been developed to assist the design professional in incorporating Comac Corporation's **ONE™** Hand Dryer into a construction project and to reduce the time and effort required to prepare project specifications.

The section numbers and titles are based on classifications and numbering contained in MasterFormat - Master List of Numbers and Titles for the Construction Industry, 1995 Edition, published jointly by the Construction Specifications Institute (CSI) and Construction Specifications Canada (CSC).

This specification section has been organized according to SectionFormat – A Recommended Format for Construction Specifications Sections, 1997 Edition, published jointly by CSI and CCS. SectionFormat provides a uniform approach to organizing specification text by placing information in three standard parts:

PART 1 – GENERAL

Describes administrative and procedural requirements.

PART 2 – PRODUCTS

Describes materials, products, and accessories to be incorporated into the construction project.

PART 3 – EXECUTION

Describes how the products will be installed at the construction site.

This specification has been written using the writing principles and techniques contained in the Manual of Practice published by CSI. The imperative mood has been used for instructions for providing, fabricating, and installing the **ONE™** Hand Dryer. It is understood that the specifications are addressed to the contractor who is legally responsible to the owner for constructing the project. Hence, the imperative mood is used to indicate actions to be performed by the contractor.



Unnecessary words such as "the", "an", and "a" have been eliminated. Streamlining has also been used to reduce verbiage. This technique places the subject first and hence provides key words for quick reference. The words "shall be" are included by inference where a colon (:) is used.

Throughout this product guide specification, references are made to other specification sections that might be contained in the project manual. These references are presented as examples and coordination reminders. For each project, these references will need to be revised to reflect actual sections being used.

Within the specification text, Imperial dimensions are presented first in brackets followed by System International Metric (SI) equivalents also in brackets. Depending on project requirements, either the Imperial or the SI metric equivalents will need to be deleted.

This product specification will need to be edited by the specifier for a specific project and to reflect the options and applications being used. The guide section has been written so that most editing can be accomplished by deleting unnecessary requirements and options. Depending on project requirements, some additional information will need to be added by the specifier. Options are indicated by []. Notes to assist the specifier in selecting options and editing the specification guide are printed in bold and indicated with *****. For final editing, all brackets and notes will need to be deleted from the guide.

.....

SECTION 10811

RAPID DRYING ELECTRIC HAND DRYER

PART 1 – GENERAL

1.1 SUMMARY

A. Section includes: Warm air, self-contained electric hand dryers.

****** List other specification sections dealing with work directly related to this section such as the following. ******

B. Related sections:

1. Section 06100 - Rough Carpentry: Blocking in stud partitions for mounting hand dryers.
2. Section 16100 - Wiring Methods: Electrical supply, conduit, wiring, boxes, and wiring devices for hand dryers.

1.2 REFERENCES

****** List by number and full title reference standards referred to in remainder of specification section. ******

A. ICC/ANSI A117.1 - International Code Council/American National Standards Institute Standard on Accessible and Useable Buildings and Facilities.

1.3 PERFORMANCE REQUIREMENTS



A. Operating protocol: Hand drying shall be accomplished by means of warm air, which simultaneously loosens and breaks up water droplets on the surface of the hands, and evaporates the liquid water.

1. Air volume in cubic feet per minute (CFM): 150

2. Heat:

a. Minimum air temperature at air outlet: [136 degrees F] [58 degrees C] when room temperature is [70 degrees F] [21 degrees C].

****** The user of the hand dryer will typically place the hands approximately 4 inches (100 mm) below the air outlet. Consequently, measurements of air velocity and temperature at this distance provide the most relevant measure of hand dryer performance. ******

b. Minimum air temperature at average hand position of [4 inches] [100 mm] below air outlet: [130 degrees F] [54 degrees C] when room temperature is [70 degrees F] [21 degrees C].

B. Drying time required to remove 5 grams of water: approximately 30 seconds

C. Moisture remaining on hands at end of drying cycle: maximum 0.2 grams.

1.4 SUBMITTALS

A. Submit in accordance with Section 01330 - Submittal Procedures:

1. Product data: Include detailed description of dryer explaining operating protocol, drying method, and performance. Provide block diagram of basic components.
2. Shop drawings showing dimensions, method of attachment, and required supports.
3. CAD drawings showing overall dimensions.
4. Electrical wiring diagrams for connection of hand dryers.
5. Manufacturer's installation and maintenance instructions.
6. Copy of warranty required by Paragraph 1.6 for review by Architect.

1.5 QUALITY ASSURANCE

A. Manufacturer: Company specializing in manufacturing, distribution and servicing of electric hand dryers.

B. Hand dryers shall be certified by Canadian Standards Association (CSA) to both US and Canadian standards and shall bear the CSA c/us mark.

****** Barrier free requirements will depend on type of project and local jurisdiction. Edit and include the following paragraph if toilet rooms and installation of hand dryers need to accommodate persons with physical disabilities. ******

C. Hand dryers shall be provided and installed in compliance with ICC/ANSI A117.1.



1.6 WARRANTY

- A. Provide under provisions of Section 01770 - Closeout Procedures: 12 year warranty for hand dryer to be free of manufacturing defects.

PARTS 2 – PRODUCTS

2.1 ACCEPTABLE MANUFACTURERS

- A. Comac Corporation, Inc., 9620b Ignace St, Brossard, Qc, CANADA J4Y 2R4; (450) 659-9899; www.comaccorporation.com
- B. [No substitutions allowed.] [Manufacturers of equivalent products submitted and approved in accordance with Section 01630 - Product Substitution Procedures.]

2.2 HAND DRYER

- A. Type: Warm air, electric hand dryer; ONE™ as manufactured by Comac Corporation, Inc.
- B. Nominal size: [10-3/8 inches wide by 13-3/4 inches high by 4 inches deep.] [263 mm wide by 349 mm high by 100 mm deep.] Conforms to ADA
- C. Weight: [20 pounds.] [9 kg.]

***** **The Universal-Voltage ONE™ Hand Dryer automatically adjusts to the following input voltages.**

- D. Power requirements: 115 or 208 or 230VAC 50 or 60Hz. 1450 watts, 12.6 amperes at 115VAC, 6.3 amperes at 230VAC

2.3 COMPONENTS

- A. Entire hand dryer mechanism is incorporated in a removable module for ease of installation and servicing:
 - 1. Module shall be connected electrically to the input power by means of a plug and receptacle. No tools shall be required to electrically connect or disconnect the module. When the module is removed, no exposed electrical contacts shall remain behind.
 - 2. Module shall be connected mechanically to the hand dryer wall plate so that it may be easily removed or installed without special tools or expertise.
- B. Combination blower and motor: Brushless, external rotor, 1800 RPM, with squirrel cage type impellor yielding air volume of 150 CFM.
- C. Heating element:
 - 1. 1380 watts resistance coil located between motor and air outlet.
 - 2. Capable of raising air temperature to [136 degrees F] [58 degrees C] measured at typical hand position of [4 inches] [100 mm] below air outlet.



3. Protected by automatic resetting thermostat to open and disconnect power to entire mechanism when airflow is restricted and close under normal operation.
- C. Air outlet: Directs air away from wall towards hands. Incorporates a series of blades to completely hide heating element from view and to shield live and moving parts from external tampering.
- D. Electronic controls: Infrared sensor automatically turns dryer on when hands are placed under air outlet and stops dryer approximately two seconds after hands are removed. Electronic sensor shuts off dryer after 60 seconds if hands are not removed or obstruction is placed under air outlet.

2.4 ENCLOSURE

****** The ONE™ Hand Dryer enclosure comprises heavy-walled zinc castings forming the sides and bottom, and a one-piece stamped steel panel forming the top and front surfaces. The zinc components may be bright or brushed chrome plated or powder coated. The steel panel may be porcelain enameled, powder coated, or produced from satin-finished stainless steel. Many combinations of materials and finishes are therefore available to satisfy the aesthetic and performance requirements of the installation. ******

- A. Material: Die-cast zinc and stamped [steel] [stainless steel].
- B. Finish:
 1. Zinc: [Bright chrome] [Brushed chrome] [Powder coated polyester].
 2. [Steel] [Stainless steel]: [Acid and scratch-resistant porcelain enamel] [Powder coated polyester] [#4 brushed satin].
- C. Colour:
 1. Zinc: [Bright chrome] [Brushed chrome] [Charcoal grey].
 2. [Steel] [Stainless steel]: [White] [Black] [Metallic Grey] [#4 brushed satin].
- D. Mounting: Cover mounted to wallplate assembly with stainless steel tamperproof screws.
- E. Wall plate: Zinc-plated steel, [0.06-inch] [1.5 mm] thick. Provided with four [1/4 inch] [6 mm] diameter holes for surface mounting to wall and one [7/8 inch] [22 mm] diameter knockout for recessed electrical wiring. Wall plate incorporates junction box for connection to surface or recessed electrical wiring and power plug for electrical connection to mechanism module.

PART 3 – EXECUTION

3.1 PREPARATION

- A. Coordinate requirements for blocking to ensure adequate means for support and installation of hand dryers.
- B. Coordinate requirements for power supply, conduit, disconnect switches, and wiring.

3.2 INSTALLATION



- A. Comply with manufacturer's installation instructions and approved shop drawings.

******* Optimum placement of hand dryers varies with layout of toilet rooms and with requirements to accommodate persons with physical disabilities. To ensure accessibility for persons with physical disabilities layout must provide a minimum clear floor space of 30 by 48 inches (762 by 1219 mm) in front of or parallel to hand dryers. A portion of the hand dryer may project into this clear space if there is a 29 inches (737 mm) minimum knee and toe space beneath the hand dryer.**

Recommended mounting heights, measured between bottom surface of hand dryer and floor, for the following users:

Men	43 inches (1092 mm)
Women	41 inches (1041 mm)
Teenagers	39 inches (991 mm)
Young children	33 inches (836 mm)
Persons with physical disabilities	35 inches (889 mm)

Mounting heights may be indicated on drawings or designated as part of this Section. To avoid potential conflicts, do not indicate mounting heights in both specifications and drawings. *****

- B. Mount dryers at [heights indicated on Drawings.] [the following heights, measured between bottom surface of hand dryer and floor:]
1. Men's toilets: [43 inches] [1092 mm].
 2. Women's toilets: [41 inches] [1041 mm].
 3. Teenager's toilets: [39 inches] [991 mm].
 4. Young children's toilets: [33 inches] [838 mm].
 5. Toilets for persons with physical handicaps: [35 inches] [889 mm].
- C. Install dryers securely to supporting substrate so that fixtures are level and aligned with each other. Use type and length of fastener as recommended by manufacturer for type of substrate.
- D. Install electrical wiring in accordance with manufacturer's instructions.

3.3 TESTING AND CLEANING

- A. Inspect installation to verify secure and proper mounting. Test each dryer to verify operation, control functions, and performance. Correct deficiencies.
- B. Clean surfaces and wash with mild soap.
- C. Protect dryers from damage from subsequent construction operations. If damage occurs, remove and replace damaged units.

END OF SECTION



Comac Corporation, Inc.
9620b Ignace St, Brossard, Qc, CANADA J4Y 2R4
Tel: (450) 659-9899 Fax: (450) 659-3412 Web: www.comaccorporation.com

COMMENTS

This product guide specification has been developed to assist the design professional in specifying the ONE™ Hand Dryer. Your comments and suggestions for future revisions are greatly appreciated. Please direct questions or comments to:

**COMAC CORPORATION, INC.
9620b Ignace St
Brossard, Qc J4Y 2R4
CANADA
Tel: (450) 659-9899
Fax: (450) 659-3412
Web: www.comaccorporation.com**